

# AMERICAN EAGLE

## LPG - NATURAL GAS LINE

### 14 - 90 kW GENERATORS

#### WINNING SETS FOR YOU AND FOR OUR PLANET!

If you want to become a champion at generating electricity with clean fuels, your smart choice is an American Eagle generator set. Powered with **Ford** or **Continental** engines, the sets in our gas line are full of standard features and ready to deliver the power you need at a very affordable price.



#### STANDARD FEATURES

- Top quality **Ford** or **Continental** spark-ignited engine, 4-cycle water-cooled.
- Brushless, class H, drip-proof, 12-lead reconnectable alternator.
- Heavy-duty skid-type steel base frame.
- Industrial silencer, protective raincap, elbow pipe, installation clamps.
- Automatic protection shutdown for abnormal temperature or pressure.
- Complete control panel with AC meters, engine gauges, battery charge voltmeter, phase selector switch, hourmeter and start key switch.
- Battery, cables, rack, installation hardware.
- Cooling radiator designed for tropical temperatures.
- Quality acrylic enamel protective paint.
- Protective steel guards to isolate fan blades.
- Rubber mounting isolators between unit and frame.
- One year limited warranty on all components.



**WIS-CON**  
TOTAL POWER CORP.

#### OPTIONAL EQUIPMENT

- Residential and critical silencer.
- Single phase upgrade alternator.
- Auto-start module.
- Weather and acoustic enclosures.
- Electronic speed governor.
- Battery trickle charger.
- Flexible exhaust connector.
- Many other options available.



#### GENERATOR SET RATINGS

GENSET MODEL	60 Hz 1800 rpm				50 Hz 1500 rpm				ENGINE MODEL	DIMENSIONS AND WEIGHT*			
	STANDBY		PRIME		STANDBY		PRIME			L in	W in	H in	Dry Wt. lb (kg)
	kW	kVA	kW	kVA	kW	kVA	kW	kVA					
AECO14SI	13.5	16.9	12.5	15.6	10.8	13.5	10	12.5	TM20	50	31	56	958 (434)
AECO18SI	18.4	23	15.6	19.5	12.4	15.5	11	13.8	TM20	50	31	56	1130 (512)
AECO25SI	25.4	31.8	21.5	26.9	18.2	22.8	15.4	19.3	TM27	59	31	56	1211 (549)
AEFO45SI	46.2	57.8	39	48.8	38.2	47.8	31.7	39.6	CSG649	71	33	57	1630 (738)
AEFO52SI	52	65	49	61.3	42	52.5	40	50	LSG875	75	35	60	1882 (853)
AEFO65SI	65	81.3	55	68.8	52	65	48	60	LSG875	75	35	60	2011 (911)
AEFO78SI	77.5	96.9	67.6	84.5	61.8	77.3	53.3	66.6	LSG875	75	35	60	2118 (959)
AEFO90SI	90.7	113.4	81	101.3	77	96.3	71	88.8	LSG875T	81	32	67	2215 (1003)

Ratings: [60 Hz]:240V; [50 Hz]:220V. Ratings applicable for both single-phase (1.0 p.f.) and 3-phase (0.8 p.f.) operation. Many industrial, commercial and residential voltages are available. Specifications are subject to change without notice. Continental is a registered trademark of Wis-Con Total Power Corp. Ford is a registered trademark of Ford Motor Company. All standard units are furnished with natural gas carburation. Please specify in your purchase order if propane carburation is needed. Proper operation on natural gas or propane requires a delivery pressure to the carburator of 10-15 inches of water (0.35-0.55 psi.) \*1 in. = 2.54 cm.

#### EAGLE GENERATOR

Toll Free (866) 289-2473 • Fax (352) 465-2910

International Info Line (352) 465-7450

PO Box 969, Dunnellon, FL 34430 USA

e-mail: [info@eaglegen.com](mailto:info@eaglegen.com)

web: [www.eaglegen.com](http://www.eaglegen.com)